

Chiller - BR 100 Y LN Low noise

Technical data 218092

Min leaving water/glycol temperature	°C	-10
Max entering water temperature	°C	15
STD ambient air temperatur	°C	35
Hydraulic pump	n°	1
Water flow	m³/h	from 11 to 29
Tot. Static pressure	kPa	from 450 to 205
Max pressure	Bar	6
Storage tank	litres	280
Water connections	mm	50 (2")

OPERATION		STANDARD	(ICE RINKS)
El. Connections	cable	4x25 mm ²	4x25 mm ²
Max abs. Power	kW	40	29
Max abs. current MRA	A	81	54
Max abs. current LRA	A	221	220
El. Supply	V/Ph/Hz	400/3/50+PE	400/3/50+PE

Sound pressure level @5m	db (A)	53*
Transport weight	kg	1.350
Operation weight	kg	1.900
Transport Length	mm	3.300
Transport Width	mm	1.250
Transport Height	mm	2.400

Optional

Connection cable 4 x 25 mm² - Flexible hoses complete with quick connect coupling 2" / 50 mm



* Free field sound pressure level taken at 1 m from the unit and 1,5 m from its base, compressors side and full operating unit without hydraulic kit. The sound pressure level may change according to the various installation and has a +/- 3 dB(A) tolerance according to ISO 3744.

Emissione: 02/22