

Chiller – BRV 50 compressor variable speed

Technical data (221054)

Min leaving water/glycol temperature	°C	+5
Max entering water temperature	°C	+10
STD ambient air temperature	°C	35
INVERTER hydraulic pump	n°	1
Water flow	m ³ /h	from 2,2 to 8,2
Tot. Static pressure	kPa	from 430 to 200
Max pressure	Bar	6
Storage tank	litres	100
Water connections	mm	50 (2")
Operation		STANDARD
El. Connections	cable	4 x 10 mm ²
Mx abs. Power	kW	20
Max abs. current MRA	A	38
Starting current LRA	A	-
El. Supply	V/Ph/Hz	400/3/50+N+PE
Sound pressure level 5 m	db (A)	55*
Transport weight	kg	480
Operation weight	kg	590
Transport Length	mm	2.250
Transport Width	mm	1.000
Transport Height	mm	2.000

Optional

Connection cable 4 x 10 mm²

Flexible hoses complete with quick connect coupling 2" / Ø 50 mm



*Free field sound pressure level taken at 1 m from the unit and 1,5 m from its base, compressors side and full operating unit without hydraulic kit. The sound pressure level may change according to the various installation and has a +/- 3 dB(A) tolerance according to ISO 3744.

Emissione: 05/21

BRENTA RENT S.r.l. Sede Legale: Via Alsazia, 3 sc. A/10 - 35127 PADOVA Cap. sociale € 12.000,00
Sede Operativa ed amministrativa: **Via dell'Industria, 17 - 35020 ARZERGRANDE (PD)**
e.mail: brenta@brentarent.it www.brentarent.it PEC: brentarent@pec.it
tel. +39 049 5800034 fax. +39 049 9724623 cell. +39 347 0554982
P.I./C.F.: 03667010288 N° REA: PD 327292

AZIENDA CON
SISTEMA DI GESTIONE QUALITA'
CERTIFICATO DA DNV
ISO 9001