

Chiller – BR 65 Y

Technical data (218014-218107)

Min leaving water/glycol temperature	°C	-10
Max entering water temperature	°C	15
STD ambient air temperature	°C	35

Hydraulic pump	n°	1
Water flow	m ³ /h	from 5.5 to 13.5
Tot. Static pressure	kPa	from 330 to 180
Max pressure	Bar	6
Storage tank	litres	200
Water connections	mm	50 (2")

Operation		STANDARD	ICE RINKS
El. Connections	cable	4G16 mm ²	4G16 mm ²
Max abs. Power	kW	24,3	17,3
Max abs. current MRA	A	52	33
Starting current LRA	A	143,5	140
El. Supply	V/Ph/Hz	400/3/50+PE	

Sound pressure level @5 m	dB(A)	53*
Transport weight	kg	800
Operation weight	kg	1.170
Transport Length	mm	3.300
Transport Width	mm	1.250
Transport Height	mm	2.400

Optional

Connection cable 4 x 16 mm²

Flexible hoses complete with quick connect coupling 2" / 50 mm



* Free field sound pressure level taken at 1 m from the unit and 1,5 m from its base, compressors side and full operating unit without hydraulic kit. The sound pressure level may change according to the various installation and has a +/- 3 dB(A) tolerance according to ISO 3744.

Emissione: 04/20

BRENTA RENT S.r.l. Sede Legale: Via Alsazia, 3 sc. A/10 - 35127 PADOVA Cap. sociale € 12.000,00
Sede Operativa ed amministrativa: **Via dell'Industria, 17 - 35020 ARZERGRANDE (PD)**
e.mail: brenta@brentarent.it www.brentarent.it PEC: brentarent@pec.it
tel. +39 049 5800034 fax. +39 049 9724623 cell. +39 347 0554982
P.I./C.F.: 03667010288 N° REA: PD 327292

AZIENDA CON
SISTEMA DI GESTIONE QUALITA'
CERTIFICATO DA DNV
ISO 9001