

Chiller – BRH 80 LN Heat pump – Low noise

Technical data (219007)

Min leaving water/glycol temperature (Summer/Winter)	°C	-10/+35
Max entering water temperature (Summer/Winter)	°C	+15/+50
STD ambient air temperature (Summer/Winter)	°C	+35/+7

Hydraulic pump	n°	1
Water flow	m ³ /h	from 5 to 14
Tot. Static pressure	kPa	from 430 to 220
Max pressure	Bar	6
Storage tank	litres	280
Water connections	mm	50 (2")

Operation		STANDARD
El. Connections	cable	4 x 25 mm ²
Max abs. Power	kW	31
Max abs. current MRA	A	60
Starting current LRA	A	153
El. Supply	V/Ph/Hz	400/3/50+PE

Sound pressure level @5 m	db (A)	51*
Transport weight	kg	1.240
Operation weight	kg	1.740
Length	mm	3.250
Width	mm	1.250
Height	mm	2.400

Optional

Connection cable 4 x 25 mm²

Flexible hoses complete with quick connect coupling 2" / Ø 50 mm



**Free field sound pressure level taken at 1 m from the unit and 1,5 m from its base, compressors side and full operating unit without hydraulic kit. The sound pressure level may change according to the various installation and has a +/- 3 dB(A) tolerance according to ISO 3744.*

Emissione: 05/19

BRENTA RENT S.r.l. Sede Legale: Via Alsazia, 3 sc. A/10 - 35127 PADOVA Cap. sociale € 12.000,00
Sede Operativa ed amministrativa: **Via dell'Industria, 17 - 35020 ARZERGRANDE (PD)**
e.mail: brenta@brentarent.it www.brentarent.it PEC: brentarent@pec.it
tel. +39 049 5800034 fax. +39 049 9724623 cell. +39 347 0554982
P.I./C.F.: 03667010288 N° REA: PD 327292

**AZIENDA CON SISTEMA
DI GESTIONE QUALITÀ
CERTIFICATO DA DNV GL
= ISO 9001 =**